

| TECHNICAL SHEET MANIPAV LASER M-3000-E | |
|-----------------------------------------------|-----------------------------------------------------------------------------------------------------------|
| WEIGHT | 900 KG |
| ENGINE | HONDA 630 |
| BATTERY | 12V /60 AH |
| PETROL TANK | 25L |
| CONTROL | ELECTRIC/HYDRAULIC |
| DRIVE | 3 HYDRAULICS ENGINES WITH GEARBOXES |
| VIBRATION | VIBRATING RULE 300 cm ELECTRIC VIBRATOR 3000 rpm |
| OIL TANK | 100 L |
| HYDRAULIC CYLINDER LASER | 40 cm HIGH |
| WHEELS | 6 UNITS. 21 “ (ANTI-PUNCTURE) |
| DISTANCE FROM THE FLOOR | 30 cm |
| LASER | MOBA “MPC” CONTROL DUAL-LASER-MATIC “LS-3000” LASER RECEPTORS 2 UNID “LASER-MATIC” PANEL CONTROL |
| TRANSPORT DIMENSIONS | |
| TOTAL LENGTH | 310 cm |
| TOTAL WIIDTH | 180 cm |
| TOTAL HEIGHT | 160 cm |
| WORK DIMENSIONS | |
| TOTAL LENGTH | 300 cm |
| TOTAL WIDTH (Vibrating rule) | 300 cm |
| TOTAL HEIGHT | 200 cm |
| LASER SUPPORT | 50 cm |
| PRODUCTION | 350 m2/h |